

Extruded tubes

PTFE pure

| Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | | Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | | Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | | | | | | |
|---------------|-------|---------------|----------------|-------|---------------|-------|---------------|----------------|-------|---------------|-------|---------------|----------------|-------|--|------|------|------|------|
| Outer | Inner | | 0 Ø | 1 Ø | Outer | Inner | | 0 Ø | 1 Ø | Outer | Inner | | 0 Ø | 1 Ø | | | | | |
| 10.0 | 4.0 | 0.16 | + 0.5 | - 0.5 | 22.0 | 6.0 | 0.80 | + 1.0 | - 1.0 | 33.0 | 20.0 | 1.40 | + 1.5 | - 1.5 | | | | | |
| | 5.0 | 0.15 | | | | | | | | 8.0 | 0.75 | | | | | | 25.0 | 1.03 | |
| | 6.0 | 0.13 | | | | | | | | 10.0 | 0.70 | | | | | | 29.0 | 0.68 | |
| | 7.0 | 0.11 | | | | | | | | 12.0 | 0.63 | | | | | | | | |
| | | | | | | | | | | 14.0 | 0.54 | | | | | 35.0 | 10.0 | 2.11 | |
| 12.0 | 5.0 | 0.23 | | | | | | | | 15.0 | 0.44 | | | | | | 12.0 | 2.04 | |
| | 6.0 | 0.21 | | | | | | | | 16.0 | 0.45 | | | | | | 16.0 | 1.86 | |
| | 8.0 | 0.17 | | | | | | | | | | | | | | | 18.0 | 1.76 | |
| | | | | | | | | | | 25.0 | 6.0 | 1.04 | | | | | | 20.0 | 1.63 |
| 14.0 | 6.0 | 0.30 | | | | | | | | 8.0 | 1.00 | | | | | | 22.0 | 1.50 | |
| | 8.0 | 0.31 | | | | | | | | 10.0 | 0.94 | | | | | | 25.0 | 1.27 | |
| | 10.0 | 0.21 | | | | | | | | 12.0 | 0.87 | | | | | | 28.0 | 1.02 | |
| | | | | | | 14.0 | 0.78 | | | | | | | | | | | | |
| 15.0 | 6.0 | 0.65 | | | | 15.0 | 0.74 | | | 40.0 | 10.0 | 2.84 | | | | | | | |
| | 8.0 | 0.31 | | | | 16.0 | 0.69 | | | | 12.0 | 2.76 | | | | | | | |
| | 10.0 | 0.25 | | | | 18.0 | 0.58 | | | | 15.0 | 2.64 | | | | | | | |
| | | | | | | 20.0 | 0.54 | | | | 20.0 | 2.30 | | | | | | | |
| 16.0 | 5.0 | 0.42 | | | | | | | | | 25.0 | 2.00 | | | | | | | |
| | 6.0 | 0.40 | | | | 27.0 | 10.0 | 1.23 | | | | 28.0 | 1.74 | | | | | | |
| | 8.0 | 0.36 | | | | 12.0 | 1.16 | | | | 30.0 | 1.55 | | | | | | | |
| | 10.0 | 0.30 | | | | 15.0 | 1.04 | | | | | | | | | | | | |
| | 12.0 | 0.23 | | | | 18.0 | 0.88 | | | 45.0 | 15.0 | 3.39 | | | | | | | |
| | | | | | | 20.0 | 0.76 | | | | 20.0 | 3.11 | | | | | | | |
| 18.0 | 5.0 | 0.54 | | | | 24.0 | 0.48 | | | | 25.0 | 2.75 | | | | | | | |
| | 6.0 | 0.52 | | | | | | | | | 30.0 | 2.30 | | | | | | | |
| | 8.0 | 0.48 | | | | 30.0 | 6.0 | 1.63 | | | 35.0 | 1.77 | | | | | | | |
| | 10.0 | 0.42 | | | | 8.0 | 1.59 | | | | 38.0 | 1.41 | | | | | | | |
| | 12.0 | 0.35 | | | | 10.0 | 1.53 | | | | | | | | | | | | |
| | | | | | | 12.0 | 1.47 | | | 50.0 | 20.0 | 3.95 | | | | | | | |
| 20.0 | 5.0 | 0.67 | | | | 14.0 | 1.38 | | | | 25.0 | 3.59 | | | | | | | |
| | 8.0 | 0.61 | | | | 15.0 | 1.34 | | | | 30.0 | 3.14 | | | | | | | |
| | 10.0 | 0.55 | | | | 18.0 | 1.18 | | | | 35.0 | 2.61 | | | | | | | |
| | 12.0 | 0.48 | | | | 20.0 | 1.06 | | | | 40.0 | 1.99 | | | | | | | |
| | 14.0 | 0.40 | | | | 22.0 | 0.93 | | | | 45.0 | 1.29 | | | | | | | |
| | 15.0 | 0.35 | | | | | | | | | | | | | | | | | |

| Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | | Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | | Diameter (mm) | | Weight (kg/m) | Tolerance (mm) | |
|---------------|-------|---------------|----------------|-------|---------------|-------|---------------|----------------|-------|---------------|-------|---------------|----------------|-------|
| Outer | Inner | | 0 Ø | 1 Ø | Outer | Inner | | 0 Ø | 1 Ø | Outer | Inner | | 0 Ø | 1 Ø |
| 55.0 | 20.0 | 4.87 | | | 70.0 | 20.0 | 8.30 | | | 105.0 | 75.0 | 11.70 | | |
| | 25.0 | 4.51 | | | | 30.0 | 7.70 | | | | 85.0 | 9.75 | | |
| | 30.0 | 4.06 | | | | 35.0 | 7.19 | | | | 90.0 | 8.36 | | |
| | 35.0 | 3.53 | | | | 40.0 | 6.70 | | | | 98.0 | 5.90 | | |
| | 40.0 | 2.91 | | | | 45.0 | 5.90 | | | | | | | |
| | 45.0 | 2.21 | | | | 50.0 | 5.30 | | | 110.0 | 75.0 | 14.25 | | |
| | 48.0 | 1.75 | | | | 55.0 | 4.28 | | | | 80.0 | 13.01 | | |
| | | | | | | 60.0 | 3.50 | | | | 90.0 | 10.27 | | |
| 60.0 | 15.0 | 6.15 | | | | 65.0 | 2.31 | | | | 95.0 | 8.52 | | |
| | 20.0 | 5.87 | | | | | | | | | 100.0 | 7.19 | | |
| | 25.0 | 5.51 | | | 80.0 | 25.0 | 10.96 | | | | | | + 3.0 | - 3.0 |
| | 30.0 | 5.06 | | | | 30.0 | 10.54 | | | 120.0 | 100.0 | 10.00 | | |
| | 35.0 | 4.53 | | | | 35.0 | 10.04 | | | | 112.0 | 7.15 | | |
| | 40.0 | 3.92 | + 2.5 | - 2.5 | | 40.0 | 9.45 | | | | | | | |
| | 45.0 | 3.22 | | | | 50.0 | 8.01 | + 2.5 | - 2.5 | 135.0 | 120.0 | 9.26 | | |
| | 50.0 | 2.10 | | | | 55.0 | 7.16 | | | | 125.0 | 7.20 | | |
| | 55.0 | 1.56 | | | | 60.0 | 6.23 | | | | | | | |
| | | | | | | 70.0 | 4.10 | | | 140.0 | 130.0 | 6.14 | | |
| 65.0 | 15.0 | 7.53 | | | | 75.0 | 2.91 | | | | | | | |
| | 20.0 | 7.37 | | | | | | | | 150.0 | 125.0 | 16.47 | | |
| | 25.0 | 7.04 | | | 90.0 | 50.0 | 11.02 | | | | 140.0 | 9.93 | | |
| | 30.0 | 6.63 | | | | 60.0 | 9.24 | | | | | | | |
| | 35.0 | 6.14 | | | | 65.0 | 8.22 | | | 160.0 | 150.0 | 7.07 | | |
| | 40.0 | 5.56 | | | | 68.0 | 7.57 | | | | | | + 5.0 | - 5.0 |
| | 45.0 | 4.95 | | | | 75.0 | 5.93 | | | 205.0 | 195.0 | 9.10 | | |
| | 50.0 | 4.15 | | | | 80.0 | 4.65 | | | | | | | |
| | 55.0 | 3.32 | | | | | | | | | | | | |
| | 60.0 | 2.14 | | | 95.0 | 80.0 | 7.49 | | | | | | | |
| | | | | | | 85.0 | 6.16 | | | | | | | |

Additional notes

Other dimensions and materials are available on request.

| | | |
|----------------------|--|-----------|
| Weights | Approximate values, products are sold by actual net weight | |
| Standard length | 2,000 mm | |
| Tolerances on length | + 20.00 mm | - 0.00 mm |

