

Extrudierte Hohlstäbe

PTFE rein

Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)		Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)		Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)	
Außen	Innen			A Ø	I Ø	Außen	Innen			A Ø	I Ø	Außen	Innen			A Ø	I Ø
10,0	4,0	0,16															
	5,0	0,15															
	6,0	0,13															
12,0	6,0	0,21															
	8,0	0,17															
14,0	6,0	0,30															
	8,0	0,31															
	10,0	0,21															
15,0	6,0	0,65															
	8,0	0,31															
	10,0	0,25															
16,0	6,0	0,40															
	8,0	0,36															
	10,0	0,30															
	12,0	0,23															
18,0	6,0	0,52															
	8,0	0,48															
	10,0	0,42															
	12,0	0,35															
20,0	6,0	0,70															
	8,0	0,65															
	10,0	0,60															
	12,0	0,49															
	14,0	0,43															
22,0	6,0	0,80															
	8,0	0,75															
	10,0	0,70															
	12,0	0,63															
	14,0	0,54															
	15,0	0,50															
	16,0	0,45															
25,0	6,0	1,04															
	8,0	1,00															
	10,0	0,94															
	12,0	0,87															
	14,0	0,78															
	15,0	0,74															
	16,0	0,69															
	18,0	0,58															
	20,0	0,54															
27,0	10,0	1,23															
	12,0	1,16															
	15,0	1,04															
	18,0	0,88															
	20,0	0,76															
30,0	8,0	1,59															
	10,0	1,53															
	12,0	1,47															
	14,0	1,38															
	15,0	1,34															
	18,0	1,18															
	20,0	1,06															
	22,0	0,93															
	25,0	0,71															
32,0	10,0	1,75															
	15,0	1,54															
	20,0	1,40															
	22,0	1,13															
	25,0	1,03															
	29,0	0,68															
35,0	10,0	2,11															
	15,0	1,89															
	18,0	1,76															
	20,0	1,63															
	22,0	1,50															
	25,0	1,27															
	28,0	1,02															
40,0	10,0	2,84															
	15,0	2,64															
	20,0	2,30															
	25,0	2,00															
	30,0	1,55															
45,0	10,0	3,36															
	15,0	3,23															
	20,0	2,93															
	25,0	2,70															
	30,0	2,30															
	35,0	1,82															
	38,0	1,03															
50,0	20,0	3,95															
	25,0	3,50															
	30,0	3,14															
	35,0	2,61															
	40,0	1,90															

Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)		Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)		Durchmesser (mm)			Gewicht (kg/m)	Toleranz (mm)					
Außen	Innen			A Ø	I Ø	Außen	Innen			A Ø	I Ø	Außen	Innen			A Ø	I Ø				
55,0	20,0	4,87			+ 2,5	- 2,5	70,0	30,0	7,25			+ 2,5	- 2,5	90,0	50,0	10,50			+ 2,5	- 2,5	
	25,0	4,51						35,0	6,80						60,0	7,30					
	30,0	4,06						40,0	6,00						65,0	7,10					
	35,0	3,53						45,0	5,90						70,0	6,30					
	40,0	2,91						50,0	4,65						75,0	5,00					
	45,0	2,21						55,0	3,90						80,0	4,00					
60,0	15,0	6,15						60,0	3,00												
	20,0	5,87					75,0	30,0	8,53						95,0	50,0					11,90
	25,0	5,51						35,0	7,94							70,0					8,30
	30,0	5,06						40,0	7,10							75,0					7,60
	35,0	4,53		45,0	6,60			80,0	7,10												
	40,0	3,92		50,0	5,80			85,0	6,16												
	45,0	3,22		55,0	4,70		100,0	50,0	13,30												
	50,0	2,10		60,0	4,25			60,0	12,10												
65,0	25,0	6,70		80,0	40,0	8,87		70,0	10,10												
	30,0	6,30		50,0	7,10			80,0	10,20												
	35,0	5,81		55,0	5,40			90,0	4,70												
	40,0	4,85		60,0	5,30																
	45,0	4,10		65,0	4,50			110,0	80,0	10,30											
	50,0	3,54		70,0	3,30				90,0	7,90											
	55,0	2,74						100,0	5,50												
				85	50,0	8,60															
					60,0	8,40		120,0	80,0	14,02											
					65,0	5,60			100,0	8,90											
					70,0	5,20															

Zusatzinformation

Andere Abmessungen und Materialien auf Anfrage.

Gewichte	ungefähre Gewichte, Verkauf erfolgt nach realem Gewicht	
Standardlänge	2.000 mm	
Toleranzen für Längen	+ 20,00 mm	- 0,00 mm